# DOMINO CORNER ELEMENT LEFT
## PRODUCT-DETAIL.MODEL-9384.302L

## STANDARD VERSION

Upholstery over foam, colors of backrest and seat can be selected separately within a fabric group. Substructure made of robust 3-layer chipboard. Sturdy skid base with plastic floor protector, powder-coated in RAL 9006 as standard. Can be linked with other DOMINO elements.

## OPTIONS

- Frame chrome plated
- Upholstery fabric TAFF B1 (P-a certified)
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric price group 3
- Upholstery fabric KUNSTLEDER B1 (P-a certified)
- Cover fabric ARTIFICIAL LEATHER B1 (price group 4)
- Upholstery fabric PROTEX B1 (P-a certified)
- Upholstery fabric PROTEX B1
- Felt floor protectors
- Linking
- 9384.904 Floor fixing set, glued or screwed

## STANDARD

FEMB level:2017 (Level 3)

DIN EN 16139, DIN EN 15372

for cover fabrics B1, optional:
highest certified fire protection safety according to DIN 66084 P-a (paper cushion test)

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| TOTAL WIDTH | ٦٩ cm |
| SEAT WIDTH | ٤٩ cm |
| TOTAL HEIGHT | ٧٥ cm |
| SEAT HEIGHT | ٤٥ cm |
| TOTAL DEPTH | ٦٩ cm |
| SEAT DEPTH | ٤٩ cm |
| WEIGHT | ٢٥ kg |

Our range of materials and colors can be found in the A2S material overview.

MADE IN GERMANY

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM

# DOMINO CORNER ELEMENT LEFT
# PRODUCT-DETAIL.MODEL-9384.302L

## BENEFITS/SPECIALS



Stable sled frame optionally chrome-plated

Durable due to high quality workmanship




Positioning the corner/outside elements

Optionally with screwed or glued floor fastening

Individually extendable through interlinkable elements

Optionally fire protection certified according to DIN 66084 P-a with cover fabric B1

## FABRIC PROPERTIES

**INTENSIVE Price group 1**
100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100
**SKANDIA Price group 1**
100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100
**FLEECE Price group 1**
100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100
**TAFF B1 Price group 2**
100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100
**WOOL Price group 3**
100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances
**PROTEX Price group 3**
surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants
**ARTIFICIAL LEATHER Price group 3**
surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances
**ARTIFICIAL LEATHER B1 Price group 4**
85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM