

# DOMINO ARMREST

## PRODUCT-DETAIL.MODEL-9384.004



### STANDARD VERSION

Upholstery over foam. Substructure made of robust 3-layer chipboard.

### OPTIONS

- Upholstery fabric TAFF B1 (P-a certified)
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric price group 3
- Upholstery fabric KUNSTLEDER B1 (P-a certified)
- Cover fabric ARTIFICIAL LEATHER B1 (price group 4)
- Upholstery fabric PROTEX B1 (P-a certified)
- Upholstery fabric PROTEX B1

### CONFIGURATION

- Upholstery fabrics | INTENSIVE Price group 1, SKANDIA Price group 1, FLEECE Price group 1, TAFF B1 Price group 2, WOOL Price group 3, PROTEX Price group 3, ARTIFICIAL LEATHER Price group 3, ARTIFICIAL LEATHER B1 Price group 4

### STANDARD

FEMB level:2017 (Level 3)

DIN EN 16139, DIN EN 15372

for cover fabrics B1, optional:  
highest certified fire protection safety according to DIN 66084 P-a (paper cushion test)

### TECHNICAL SPECIFICATIONS

TOTAL WIDTH	22 cm
TOTAL HEIGHT	02 cm
TOTAL DEPTH	19 cm
WEIGHT	9 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@ass.de  
WWW.A2S.COM

# DOMINO ARMREST

## PRODUCT-DETAIL.MODEL-9384.004



### BENEFITS/SPECIALS



Armrest element to extend the DOMINO series



Individually extendable through interlinkable elements



Optionally fire protection certified according to DIN 66084 P-a with cover fabric B1

### FABRIC PROPERTIES

#### **INTENSIVE Price group 1**

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

#### **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

#### **FLEECE Price group 1**

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

#### **TAFF B1 Price group 2**

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

#### **WOOL Price group 3**

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

#### **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

#### **ARTIFICIAL LEATHER Price group 3**

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

#### **ARTIFICIAL LEATHER B1 Price group 4**

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants