

# CYLINDA UPHOLSTERED STOOL 1-SEATER

## PRODUCT-DETAIL.MODEL-9359.045



### STANDARD VERSION

Upholstery over foam. Substructure made of robust 3-layer chipboard. With plastic floor protector.

### OPTIONS

- Felt floor protectors
- Upholstery fabric TAFF B1 (P-a certified)
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric price group 3
- Upholstery fabric KUNSTLEDER B1 (P-a certified)
- Cover fabric ARTIFICIAL LEATHER B1 (price group 4)
- Upholstery fabric PROTEX B1 (P-a certified)
- Upholstery fabric PROTEX B1
- 9359.945 1-seater floor mounting set, glued or screwed

### STANDARD

DIN EN 16139, DIN EN 15372

FEMB level:2017 (Level 3)

for cover fabrics B1, optional:

highest certified fire protection safety according to DIN 66084 P-a (paper cushion test)

### TECHNICAL SPECIFICATIONS

SEAT WIDTH	£0 cm
TOTAL HEIGHT	£1 cm
SEAT HEIGHT	£1 cm
SEAT DEPTH	£0 cm
DIAMETER	£0 cm
WEIGHT	Λ kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@ass.de  
WWW.A2S.COM

# CYLINDRA UPHOLSTERED STOOL 1-SEATER

## PRODUCT-DETAIL.MODEL-9359.045



### BENEFITS/SPECIALS



Optionally with screwed or glued floor fastening



Optionally fire protection certified according to DIN 66084 P-a with cover fabric B1



Ideal as an extension for lounge areas



Available in different sizes

### FABRIC PROPERTIES

#### **INTENSIVE Price group 1**

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

#### **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

#### **FLEECE Price group 1**

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

#### **TAFF B1 Price group 2**

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

#### **WOOL Price group 3**

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

#### **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

#### **ARTIFICIAL LEATHER Price group 3**

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

#### **ARTIFICIAL LEATHER B1 Price group 4**

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants