

CYLINDA UPHOLSTERED STOOL 2-SEATER

PRODUCT-DETAIL.MODEL-9359.090



STANDARD VERSION

Upholstery over foam. Substructure made of robust 3-layer chipboard. With plastic floor protector.

OPTIONS

- Felt floor protectors
- Upholstery fabric TAFF B1 (P-a certified)
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric price group 3
- Upholstery fabric KUNSTLEDER B1 (P-a certified)
- Cover fabric ARTIFICIAL LEATHER B1 (price group 4)
- Upholstery fabric PROTEX B1 (P-a certified)
- Upholstery fabric PROTEX B1
- 9359.990 2-seater floor mounting set, glued or screwed

STANDARD

DIN EN 16139, DIN EN 15372

FEMB level:2017 (Level 3)

for cover fabrics B1, optional:

highest certified fire protection safety according to DIN 66084 P-a (paper cushion test)

TECHNICAL SPECIFICATIONS

SEAT WIDTH	90 cm
TOTAL HEIGHT	81 cm
SEAT HEIGHT	81 cm
SEAT DEPTH	90 cm
DIAMETER	90 cm
WEIGHT	21 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM

CYLINDRA UPHOLSTERED STOOL 2-SEATER PRODUCT-DETAIL.MODEL-9359.090



BENEFITS/SPECIALS



Optionally with screwed or glued floor fastening



Optionally fire protection certified according to DIN 66084 P-a with cover fabric B1



Ideal as an extension for lounge areas



Available in different sizes

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants