

# CHILL CUSHION

## PRODUCT-DETAIL.MODEL-5031.001



### STANDARD VERSION

Inner bag with EPS polystyrene ball filling according to DIN 4102 B1 flame retardant.  
Upholstery fabric with stitched edge, removable by zipper, washable or wipeable depending on fabric group.

### OPTIONS

- Upholstery fabric NORDIC
- Upholstery fabric OUTSIDE
- Upholstery fabric PROTEX (price group 3)


### CONFIGURATION

- Upholstery fabrics | NORDIC, OUTSIDE, OX, PRO B1, PROTEX

### TECHNICAL SPECIFICATIONS

TOTAL WIDTH	110 cm
TOTAL HEIGHT	27 cm
LYING SURFACE HEIGHT	27 cm
TOTAL DEPTH	120 cm
LYING SURFACE DEPTH	120 cm
WEIGHT	1 kg

### BENEFITS/SPECIALS



Cover removable by zipper

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@ass.de  
WWW.A2S.COM

# CHILL CUSHION

## PRODUCT-DETAIL.MODEL-5031.001



### FABRIC PROPERTIES

#### **NORDIC**

100% polyester | 330 g/m<sup>2</sup> | 100,000 Martindale rubs | Linting 4 - 5 | ÖKO-Tex 100 | 60°C washable

#### **OUTSIDE**

Imitation leather 83% PVC, 15% PES, 2% PU | flame retardant according to EN 1021 1&2 | 600 g/m<sup>2</sup> | 120,000 Martindale rubs | no linting | tested for harmful substances | washable, waterproof

#### **OX**

100% polyester with PVC coating | 374 g/m<sup>2</sup> | 60,000 Martindale rubs | no linting | tested for harmful substances | 40°C washable, wipeable, water resistant

#### **PRO B1**

100% polyester | flame retardant (building material class B1) according to DIN 4102-1 | 400 g/m<sup>2</sup> | 80.000 Martindale rubs | 60° C washable | ÖKO-Tex® 100

#### **PROTEX**

Surface 100% vinyl / fabric 100% polyester | flame-retardant in accordance with EN 1021 1&2, DIN 4102 B2 | weight 685 g/m<sup>2</sup> | 300,000 Martindale cycles | no linting

**SPECIAL PROPERTIES:** PERMABLOK3® - protection against germs, abrasion and stains: Antibacterial, antifungal, stain protection, resistance to sulphide stains, anti-fungal protection - mould-resistant backing layer and surface | resistant to disinfectants, easy cleaning - wipeable with soap and water | antistatic surface

**Tested according to:** ISO206B02 7/8 UV resistance | ISO 18184 & ISO 21702 Virus-free surface to reduce coronavirus | ISO 22196 for bacteria-free surface | ISO 16000 indoor air emission class A+

**Tested for:** Plasticisers and harmful substances - material requirements of the toy standards EN 71-3 Safety of toys (migration of certain elements) and 2005/84/EC (phthalates in toys and childcare articles)