

CHANGE SLED BASE CHAIR

PRODUCT-DETAIL.MODEL-7802



STANDARD VERSION

PAGHOLZ® waisted shell, with ergonomic three-dimensional shell shape and handle slot. Surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish created in the pressing process. Edges and waist are milled. Sled base, round tube: 16/2 mm, seat shell with movable bearings, chrome-plated. With plastic floor protector.

OPTIONS

- Seat upholstery price group 1
- Seat and back cushion price group 1
- Seat upholstery price group 2
- Seat and back cushion price group 2
- Seat upholstery price group 3
- Seat and back cushion price group 3
- Seat upholstery price group 4
- Seat and back cushion price group 4
- Felt floor protectors
- PAGHOLZ® Color Wood - Price group 2
- PAGHOLZ® COLOUR WOOD

CONFIGURATION

- الملون PAGHOLZ® خشب
- PAGHOLZ® Colour Wood
- PAGHOLZ® Colour Wood
- ألوان الإطار

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

120 kg

SIZES

SIZE	6
CHAIR WIDTH	01 cm
CHAIR HEIGHT	10 cm
SEAT HEIGHT	17 cm
CHAIR DEPTH	00 cm
STACKABILITY	5 pcs.
WEIGHT	1 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM

CHANGE SLED BASE CHAIR PRODUCT-DETAIL.MODEL-7802



BENEFITS/SPECIALS



PAGHOLZ® from sustainable forestry



Optionally with seat and backrest upholstery



Colour deviations possible



Indestructible PAGHOLZ® shell, scratch, break and impact resistant; flame retardant




Slender, stable sled frame



Shell design allows different seating positions, even reverse



Stackable up to 7 chairs (without upholstery)



Flexible seat shell ensures good blood circulation in the muscles

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants