WOODMARK C-SHAPE SLED BASE CHAIR WITH SEAT UPHOLSTERY

PRODUCT-DETAIL.MODEL-7105





STANDARD VERSION

Seat and back separate and shaped to fit the body. Made of multiplex, surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish produced in the pressing process.

Seat with flat upholstery.

C-shape frame, side part oval tube: 35/15/2 mm, seat support rectangular tube: 30/15/2 mm, cross strut oval tube: 35/15/1.5 mm, standard version epoxy coated. Including plate protector to sit on the table top. Floor protector with step protection.

OPTIONS

- WOODMARK maple D033 or gray white U023
- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Back stained in colorSeat and back riveted

- Felt floor protectors
- Row connection

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

170 kg

SIZES

SIZE	6	7
CHAIR WIDTH	80 cm	80 cm
CHAIR HEIGHT	V9 cm	۸۳ cm
SEAT HEIGHT	ελ cm	0Y cm
CHAIR DEPTH	01 cm	01 cm
STACKABILITY	-	_
WEIGHT	V kg	V kg

Our range of materials and colors can be found in the A2S material overview.









WOODMARK C-SHAPE SLED BASE CHAIR WITH SEAT UPHOLSTERY

PRODUCT-DETAIL.MODEL-7105



BENEFITS/SPECIALS



Floor protectors with integrated step protection




Plate protectors protect the table when stacking



Seat and back concealed screwed



With seat upholstery



Optionally with row connection



Stable and solid C-shape frame



Seat and back melamine coated: scratch, break and impact resistant; flame retardant



No disturbance of the chair legs when getting in and out of the chair

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100 SKANDIA Price group 1

100% polyester | flame retardant according to EN 10211 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100 FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100 TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100 WOOL Price group 3

100% wool | flame retardant according to EN 10211&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants