MODULA BENCH 45° CONVEX WITH BACKREST
PRODUCT-DETAIL.MODEL-9384.245



STANDARD VERSION

Upholstery over foam, colors of backrest and seat can be selected separately within a fabric group. Substructure made of robust 3-layer chipboard. Sturdy skid base with plastic floor protector, powder-coated in RAL 9006 as standard. Can be linked with other DOMINO elements.

OPTIONS

- Upholstery fabric TAFF B1 (P-a certified)
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric price group 3
- Upholstery fabric KUNSTLEDER B1 (P-a certified)
- Cover fabric ARTIFICIAL LEATHER B1 (price group 4)
- Upholstery fabric PROTEX B1 (P-a certified)
- Upholstery fabric PROTEX B1
- Frame chrome plated
- 9384.904 Floor fixing set, glued or screwed

STANDARD

FEMB level:2017 (Level 3)

GS-zertifiziert gem. DIN EN 16139, DIN EN 1023-1, DIN EN 1023-2, DIN EN 16121, DIN EN 15372

for cover fabrics B1, optional:
highest certified fire protection safety according to DIN 66084 P-a (paper cushion test)

TECHNICAL SPECIFICATIONS

TOTAL WIDTH	١٦١ cm
TOTAL HEIGHT	٧٥ cm
SEAT HEIGHT	٤٥ cm
TOTAL DEPTH	٦٩ cm
SEAT DEPTH	٤٩ cm
WEIGHT	٣٧ kg

Our range of materials and colors can be found in the A2S material overview.

MADE IN GERMANY

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM

MODULA BENCH 45° CONVEX WITH BACKREST
PRODUCT-DETAIL.MODEL-9384.245

BENEFITS/SPECIALS



Stable sled frame optionally chrome-plated

Durable due to high quality workmanship

Optionally with screwed or glued floor fastening

Optionally fire protection certified according to DIN 66084 P-a with cover fabric B1



Can be individually extended with MAZE and straight DOMINO seating elements

Can be combined with CYLINDA, BLOC and COMBi series

FABRIC PROPERTIES

INTENSIVE Price group 1
100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100
SKANDIA Price group 1
100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100
FLEECE Price group 1
100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100
TAFF B1 Price group 2
100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100
WOOL Price group 3
100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances
PROTEX Price group 3
surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants
ARTIFICIAL LEATHER Price group 3
surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances
ARTIFICIAL LEATHER B1 Price group 4
85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM