

SOLID BRIDGE TABLE (200X80 CM) PRODUCT-DETAIL.MODEL-3111.208



STANDARD VERSION

Note: Number of seats refers to combination with matching SOLID bench.

Tabletop and side panels, 3-layer chipboard (E1) according to DIN EN 312, melamine coated according to DIN EN 14322, highly abrasion-resistant, with 2 mm plastic edge, thickness: 38 mm. Flame retardant, certified according to DIN 4102-B1.

Panel, 3-layer chipboard (E1) according to DIN EN 312, melamine coated according to DIN EN 14322, highly abrasion-resistant, with 2 mm plastic edge, thickness: 19 mm. Flame retardant, certified according to DIN 4102-B1.

With integrated cable channel under the table top, rear.

OPTIONS

- Floor mounting
- Cable opening, Ø 80 mm
- 0187 Multimedia bar
- Table top finishes price group 2
- 0905 Multimedia socket, Ø 80 mm
- Felt floor protectors

STANDARD

GS-zertifiziert gem. DIN EN 15372 (Tische), DIN EN 16139 (Bänke)

SIZES

TABLE WIDTH	200 cm
TABLE HEIGHT	70 cm
TABLE DEPTH	80 cm
STACKABILITY	-
NUMBER OF SEATS	4
WEIGHT	110 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM

SOLID BRIDGE TABLE (200X80 CM) PRODUCT-DETAIL.MODEL-3111.208




BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Optionally with side cable aperture



Optionally with floor mounting



With integrated cable duct, rear



Support panel material flame-retardant according to DIN 4102 B1