

4-LEG SOLID WOOD CHAIR WITH SEAT AND BACK UPHOLSTERY

PRODUCT-DETAIL.MODEL-5263



STANDARD VERSION

Seat and back separately, shaped to fit the body. Made of beech plywood. Edges softly rounded. Environmentally friendly lacquered with water-based varnish.

4-legged frame, dowelled, beech solid wood studs, semicircular: 55/30 mm. Environmentally friendly lacquered with water-based varnish. With plastic floor protector.

Seat and back covered all around with full upholstery.

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Felt floor protectors

CONFIGURATION

- Upholstery fabrics | INTENSIVE Price group 1, SKANDIA Price group 1, FLEECE Price group 1, TAFF B1 Price group 2, WOOL Price group 3, PROTEX Price group 3, ARTIFICIAL LEATHER Price group 3, ARTIFICIAL LEATHER B1 Price group 4

STANDARD

GS-zertifiziert gem. DIN EN 16139

LOAD CAPACITY

120 kg

SIZES

SIZE	6
CHAIR WIDTH	01 cm
CHAIR HEIGHT	11 cm
SEAT HEIGHT	EV cm
CHAIR DEPTH	00 cm
STACKABILITY	-
WEIGHT	1 kg

Our range of materials and colors can be found in the A2S material overview.




A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@ass.de
WWW.A2S.COM

4-LEG SOLID WOOD CHAIR WITH SEAT AND BACK UPHOLSTERY

PRODUCT-DETAIL.MODEL-5263



BENEFITS/SPECIALS



Body shaped seat and back



Solid beech wood from sustainable forestry with water-based varnish



Painted with environmentally friendly water-based paint.

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants