

SOLID BRIDGE TABLE (200X80 CM) MODEL 3111.208



STANDARD VERSION

Note: Completely dismountable system.

Note: Number of seats refers to combination with matching SOLID bench.

Tabletop and side panels, 3-layer chipboard (E1) according to DIN EN 312, melamine coated according to DIN EN 14322, highly abrasion-resistant, with 2 mm plastic edge, thickness: 38 mm. Flame retardant, certified according to DIN 4102-B1.

Panel, 3-layer chipboard (E1) according to DIN EN 312, melamine coated according to DIN EN 14322, highly abrasion-resistant, with 2 mm plastic edge, thickness: 19 mm. Flame retardant, certified according to DIN 4102-B1.

With integrated cable channel under the table top, rear.

OPTIONS

- Floor mounting
- Cable opening, Ø 80 mm
- 2-fold socket with network connection
- Table top finishes price group 2
- 2-way socket with USB port

STANDARD

GS-zertifiziert gem. DIN EN 15372 (Tische), DIN EN 16139 (Bänke)

SIZES

TABLE WIDTH	200 cm
TABLE HEIGHT	75 cm
TABLE DEPTH	80 cm
STACKABILITY	-
NUMBER OF SEATS	4
WEIGHT	85 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

SOLID BRIDGE TABLE (200X80 CM) MODEL 3111.208




BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Optionally with side cable aperture



Optionally with floor mounting



With integrated cable duct, rear



Optionally two socket outlets each with USB port or network connection: 1x center, 1x left, 1x right or both sides



Support panel material flame-retardant according to DIN 4102 B1