

#### STANDARD VERSION

Top, 3-layer chipboard (E1), melamine coated, highly abrasion resistant, with 3 mm plastic edge, thickness: 25 mm.

#### **OPTIONS**

- Decoration group 2
- magnetic
- Cover fabric Intensive
- Cover fabric Skandia
- Cover fabric fleece
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric WOOL (price group
- Frame chrome plated

# TECHNICAL SPECIFICATIONS

WIDTH HEIGHT 46 cm WEIGHT 15 kg

### **BENEFITS/SPECIALS**



Mounting by means of Allen screw on the table top



Connection of T-shaped partitions



Optionally with fabric cover



Ideal as a view and sound insulation

# **FABRIC PROPERTIES**

#### INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

# SKANDIA Price group 1

 $100\% \ polyester \ | \ \bar{flame} \ retardant \ according \ to \ EN \ 1021 \ 1 \ | \ 245 \ g/m2 \ +/-5\% \ | \ 70,000 \ Martindale \ tours \ | \ linting \ 4-5 \ | \ \ddot{O}KO-Tex$ 100 FLEECE Price group 1

## 100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex

TAFF B1 Price group 2 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5

## LÖKO-Tex 100

harmful substances

WOOL Price group 3 100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for