

FLEX 4-LEG CHAIR

MODEL 7874



STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

4-leg frame, round tube: 0.87"/0.10", standard version epoxy coated. With articulated floor protector.

OPTIONS

- Felt joint floor protectors
- Chair frame chrome plated
- Book tray (size 5-7)
- Teflon floor protector
- Fully upholstered FLEX (size 5-7)

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

LOAD CAPACITY

276 lb

SIZES

SIZE	2	3	4	5	6	7
CHAIR WIDTH	16.93 "	17.32 "	17.72 "	20.47 "	21.26 "	20.87 "
CHAIR HEIGHT	24.41 "	25.98 "	27.17 "	31.10 "	32.28 "	34.25 "
SEAT HEIGHT	12.20 "	13.78 "	14.96 "	16.93 "	18.11 "	20.08 "
CHAIR DEPTH	13.78 "	14.17 "	14.57 "	21.65 "	21.26 "	22.44 "
STACKABILITY	3 pcs.	3 pcs.	3 pcs.	3 pcs.	3 pcs.	3 pcs.
WEIGHT	6 lb	6 lb	9 lb	12 lb	12 lb	12 lb

Our range of materials and colors can be found in the A2S material overview.




A2S-Furnishing Systems Ltd.
 ASS-Einrichtungssysteme GmbH
 info@a2s.com
 WWW.A2S.COM

FLEX 4-LEG CHAIR MODEL 7874



BENEFITS/SPECIALS



Easy to carry due to low weight




Optionally with book tray from size 5



Optional seat shell fully upholstered from size 5 onwards



Seat shell with integrated ventilation channel



Robust 4-leg frame



Stackable up to 3 chairs
(without upholstery)

FABRIC PROPERTIES

FLEX upholstery

Flame retardant according to DIN 4102 B1 | 8.82 oz/yd² +/-5% | 40,000 Martindale tours | Linting 4 | ÖKO-Tex 100