PREMIUM OFFICE SWIVEL CHAIR WITH MESH BACKREST AND 3D ARMRESTS MODEL 9348.002





STANDARD VERSION

Fully upholstered seat and black mesh back. Synchronous dynamic movement with locking of the back in 5 positions. Seat inclination and seat depth adjustable: back 20°, seat 6° as well as seat depth adjustment range 2.36". Backrest 22.05" high, with independent lumbar support adjustment. 5-star aluminum base, with infinitely variable gas lift height adjustment including seat depth suspension: 17.72" - 22.05". Polished aluminum base, with load-dependent braked safety casters.

Includes 3D armrests in soft plastic, height adjustable by 3.15", width adjustable by 1.18", adjustable forwards and backwards by 1.97".

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3

STANDARD

DIN EN 1729-1, DIN EN 1729-2

SIZES

CHAIR WIDTH	27.17 "
CHAIR HEIGHT	41.34-45.67 "
SEAT HEIGHT	17.72-22.05 "
CHAIR DEPTH	27.17 "
STACKABILITY	-
WEIGHT	34 lb

Upholstery fabric price group 4

Soft casters for hard floors

LOAD CAPACITY

243 lb

Our range of materials and colors can be found in the A2S material overview.



PREMIUM OFFICE SWIVEL CHAIR WITH MESH BACKREST AND 3D ARMRESTS MODEL 9348.002



BENEFITS/SPECIALS



Elegant, high-quality aluminum base



Stepless gas lift height adjustment includes seat depth suspension

SKANDIA Price group 1

FLEECE Price group 1

TAFF B1 Price group 2

PROTEX Price group 3

surface, resistant to disinfectants
ARTIFICIAL LEATHER Price group 3

tours | no linting | tested for harmful substances ARTIFICIAL LEATHER B1 Price group 4

WOOL Price group 3

FABRIC PROPERTIES



Load-dependent braked safety casters prevent unintentional rolling away



Self-weighing synchronous mechanism automatically adjusts spring force or resistance

no linting tested for harmful substances resistant to blood and urine, resistant to disinfectants



Black mesh backrest, with lumbar support adjustment

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

100% polyester | flame retardant according to EN 10211 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

100% polyester | flame retardant according to EN 10211&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

100% wool flame retardant according to EN 10211&2 16.23 oz/y² +/-5% 35,000 Martindale tours linting 4 tested for harmful substances

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/ γ^2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y² +/-10% | 100,000 Martindale

85% PVC compound, 15% cotton knit flame retardant according to EN 1021 1&2, DIN 4102 B1 weight 27.51+/-1.76 oz/y² 75,000 Martindale tours



Ergonomically shaped, breathable mesh backrest



Armrest three-dimensionally adjustable