GAS LIFT SWIVEL CHAIR WITH FOOT RING MODEL 8377.202





STANDARD VERSION

Waisted, angular seat shell, shaped to fit the body. Made of multiplex, consisting of beech plywood, veneered lengthwise. Standard in beech multiplex natural, environmentally friendly lacquered with water-based lacquer, edges softly rounded.

Plastic 5-star base in black, with infinitely variable gas lift height adjustment. Round tubular column: 1.97". Version with elevation and heightadjustable foot ring, chrome-plated. With plastic feet.

OPTIONS

- Multiplex COLOUR WOOD
- Handle hole
- Seat upholstery price group 1 (size 6, 7)
- Backrest upholstery price group 1 (size 6, 7)

STANDARD

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

SIZES

SIZE	5-7
CHAIR WIDTH	24.80 "
CHAIR HEIGHT	32.68-40.55 "
SEAT HEIGHT	4.33-20.08 "
CHAIR DEPTH	24.80 "
STACKABILITY	-
WEIGHT	18 lb

- Seat upholstery price group 2 (size 6, 7)
- Backrest upholstery price group 2 (size 6, 7)
- Seat upholstery price group 3 (size 6, 7)
- Backrest upholstery price group 3 (size 6, 7)
- Seat upholstery price group 4 (size 6, 7)
- Backrest upholstery price group 4 (size 6, 7)
- Felt floor protectors
- Load-dependent braking casters (SH +1.18")

LOAD CAPACITY

276 lb

Our range of materials and colors can be found in the A2S material overview.

A2S-Furnishing Systems Ltd. ASS-Einrichtungssysteme GmbH info@a2s.com WWW.A2S.COM





GAS LIFT SWIVEL CHAIR WITH FOOT RING MODEL 8377.202



BENEFITS/SPECIALS



trapezoidal shape (not with

backrest upholstery)

Elevation with chrome-plated Optionally with handle hole in foot ring, height adjustable



Height adjustment by safety das sprind



Optionally with loaddependent braked casters



Optionally with seat and backrest upholsterv



Seat shell environmentally friendly lacquered with waterbased varnish



Body contoured seat shell

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100 **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 10211 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100 FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100 TAFF B1 Price group 2

100% polyester | flame retardant according to EN 10211&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100 WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y² | 300,000 Martindale tours | no linting wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y² +/-10% | 100,000 Martindale tours no linting tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51+/-1.76 oz/y² | 75,000 Martindale tours | no linting tested for harmful substances resistant to blood and urine, resistant to disinfectants