

# 4-LEG TABLE, METAL WELDED MODEL 1001.066



## STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 0.12" plastic edge, thickness: 0.98".

**Note:** Table height specifications refer to a tabletop thickness of 0.98".

4-leg base frame, side parts round tube: 40/2 mm, frame square tube welded and rounded: 40/20/2 mm. Frame epoxy coated, with plastic floor protector with level compensation.

Table top shape: rectangular

**ATTENTION:** Observe chair frame width!

## OPTIONS

- Table top finishes price group 2
- Table top HPL glued
- Table top compact board 0.47"
- Table top with 40 mm corner radius
- Cable opening, Ø 3.15"
- Cable opening, Ø 3.54"
- Mesh cable duct
- Felt floor protectors
- Teflon floor protector
- Fixed castor
- Table frame chrome plated
- Height adjustment 3-7
- Cable slack
- Cable clamp Ø 38-40 mm
- 6-fold gounded socket

## STANDARD

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2, DIN EN 15372

FEMB level:2017 (Level 3)

## SIZES

SIZE	3	4	5	6	7	72 cm	75 cm
TABLE WIDTH	23.62 "	23.62 "	23.62 "	23.62 "	23.62 "	23.62 "	23.62 "
TABLE HEIGHT	22.83 "	25.20 "	27.56 "	29.92 "	32.28 "	28.35 "	29.53 "
TABLE DEPTH	23.62 "	23.62 "	23.62 "	23.62 "	23.62 "	23.62 "	23.62 "
STACKABILITY	-	-	-	-	-	-	-
NUMBER OF SEATS	1	1	1	1	1	1	1
WEIGHT	24 lb	25 lb	26 lb	29 lb	30 lb	28 lb	29 lb

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM


# 4-LEG TABLE, METAL WELDED MODEL 1001.066



## BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Optional compact board as table top




Optional table top with 40 mm corner radius



Floor saver with level compensation compensates for uneven floors



Optional frame mobile by means of 2 fixed castors



Optional melamine coated table top with ASSODUR® edge