SOLID BRIDGE TABLE (160X80 CM)
MODEL 3111.168

STANDARD VERSION

Note: Completely dismountable system.
Note: Number of seats refers to combination with matching SOLID bench.
Tabletop and side panels, 3-layer chipboard (E1) according to DIN EN 312, melamine coated according to DIN EN 14322, highly abrasion-resistant, with 2 mm plastic edge, thickness: 38 mm. Flame retardant, certified according to DIN 4102-B1.
Panel, 3-layer chipboard (E1) according to DIN EN 312, melamine coated according to DIN EN 14322, highly abrasion-resistant, with 2 mm plastic edge, thickness: 19 mm. Flame retardant, certified according to DIN 4102-B1.
With integrated cable channel under the table top, rear.

OPTIONS

- Floor mounting
- Table top finishes price group 2
- Cable opening, Ø 3.15"
- 0905 Multimedia socket, Ø 80 mm
- 2-way socket with USB port
- 2-fold socket with network connection

STANDARD

GS-zertifiziert gem. DIN EN 15372 (Tische), DIN EN 16139 (Bänke)

SIZES

TABLE WIDTH	62.99 "
TABLE HEIGHT	29.53 "
TABLE DEPTH	31.50 "
STACKABILITY	–
NUMBER OF SEATS	3
WEIGHT	161 lb

Our range of materials and colors can be found in the A2S material overview.

MADE IN GERMANY

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

SOLID BRIDGE TABLE (160X80 CM)
MODEL 3111.168

BENEFITS/SPECIALS

Melamine coated table top with robust plastic edge

Optionally with side cable aperture

Optionally with floor mounting

With integrated cable duct, rear

Optionally two socket outlets each with USB port or network connection: 1x center, 1x left, 1x right or both sides

Support panel material flame-retardant according to DIN 4102 B1

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM