4-LEG SOLID WOOD CHAIR WITH SEAT AND BACK UPHOLSTERY MODEL 5273





STANDARD VERSION

Seat and back separately, shaped to fit the body. Made of beech plywood. Edges softly rounded. Environmentally friendly lacquered with water-based varnish.

4-legged frame, dowelled, beech solid wood studs, semicircular: 55/30 mm. Environmentally friendly lacquered with water-based varnish. With plastic floor protector.

Seat and back covered all around with full upholstery.

Frame incl. armrests.

OPTIONS

- Chair colored stained
- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4

Felt floor protectors

STANDARD

GS-zertifiziert gem. DIN EN 16139

LOAD CAPACITY

276 lb

SIZES

CHAIR WIDTH	22.44 "
CHAIR HEIGHT	31.69 "
SEAT HEIGHT	18.31 "
CHAIR DEPTH	21.65 "
STACKABILITY	_
WEIGHT	21 lb

Our range of materials and colors can be found in the A2S material overview.





4-LEG SOLID WOOD CHAIR WITH SEAT AND BACK UPHOLSTERY MODEL 5273



BENEFITS/SPECIALS







Comfortable armrests



Solid beech wood from sustainable forestry with water-based varnish



Painted with environmentally friendly water-based paint.

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100 SKANDIA Price group 1

100% polyester | flame retardant according to EN 10211 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100 FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100 WOOL Price group 3

100% wool | flame retardant according to EN 10211&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/ y^2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y 2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit \int flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51+/-1.76 oz/y² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants